

BUBBLE PRESSURE TENSIOMETER – BPT MOBILE

SPECIFICATIONS



KRÜSS

Advancing your Surface Science

Product group specifications**BPT Mobile****Pressure measurement**

Maximum pressure	1.25 kPa
Precision	2 %

Data output

USB	Microsoft Excel (XML format)
-----	------------------------------

Measurement specifications**BPT Mobile****Bubble pressure**

Results	dynamic surface tension vs. surface age	dynamic surface tension at constant surface age	single dynamic surface tension
Surface tension range		15 to 100 mN/m	
Resolution		0.1 mN/m	
Precision		2 %	
Surface age range		10 to 30.000 ms	
Resolution		1 ms	
Surface age range		10 %	

General specifications**BPT Mobile****Sample dimensions**

Minimum recommended sample volume 15 mL ¹⁾

Temperature measurement

Range 0 to 100 °C

Resolution 0.1 °C

Location sample

Housing and peripherals

Touch display integrated color IPS display (180 × 854 px, size 5")

Stand optional

Environment

Operating temperature 5 to 60 °C

Humidity without condensation

Instrument dimensions

Size 85 mm × 55 mm (W × D)

Height 220 mm

Weight (without accessories) 600 g

Power supply

Voltage 5 V (powered by USB)

Power consumption 2.5 W

Interfaces

PC USB-Micro-B

¹⁾ sample vessel SV13 recommended

